

SL ANCHOR STRAPS



CLASSIFIED TO NFPA 2500
GENERAL USE

SCAN FOR
MORE DETAILS



Our SL Anchor Straps are strong, versatile, and lightweight. Classified to NFPA General Use, the SL Anchor Straps have a high breaking strength to withstand heavy loads on the system. They are built to last using proof-loaded steel hardware and durable, weather-resistant polyester webbing. Supple, compact, and quick to deploy, the SL Anchor Straps bend easily around structures and feed smoothly through metal grating. Their bright red color is highly visible and their contrasting gray stitching aids inspection.

Shared Features

- Single-layer design is compact and light - easy to pack, carry, and deploy
- Proof-loaded steel hardware and weather-resistant polyester webbing
- Polyester is more resistant to UV & water, and has less elongation than nylon
- Supple and pliable - bends easily around structures and metal grating
- Red for high visibility with contrasting gray stitching to aid inspection
- Combines with anchor sleeves & edge guards to add versatility & durability

SL FastLink™ Anchor Strap

- Fastest connecting anchor strap available
- Designed to mitigate tri-axial & cross-loading
- Rapidly installed by clipping included carabiner to integrated quick link
- Quick link functions as single focal point, mitigating tri-axial and cross-loading
- Strength Specifications - Basket (U): 45 kN, Choker: N/A, End-to-End: 22 kN

SL Anchor Strap

- Steel D-Rings sized to pass through one another for easy Choker configuration
- Simple and efficient workhorse for building technical rope systems
- Minimalist design is low-profile, easy to carry, and smooth-handling
- Strength Specifications - Basket (U): 62 kN, Choker: 30 kN, End-to-End: 29 kN

SL Variable Anchor Strap

- Strap length is easily adjusted from 3ft to 7ft, increasing versatility
- Quickly set the desired length, even after rigging in Choker (Girth Hitch)
- Additional length of webbing withstands high load before slipping
- Steel adjuster buckle meets strength specifications without back-up knot
- Steel D-Rings sized to pass through one another for easy Choker configuration
- Strength Specifications - Basket (U): 54 kN, Choker: 28 kN, End-to-End: 20 kN



SL Anchor Strap

SL FastLink Anchor Strap



Variable Anchor Strap

Item #	Product	Size	Length	Weight
201072	SL FastLink Anchor Strap	Small	91 cm (3 ft)	0.52 kg (1.14 lb)
201073	SL FastLink Anchor Strap	Medium	152 cm (5 ft)	0.59 kg (1.29 lb)
201074	SL FastLink Anchor Strap	Large	213 cm (7 ft)	0.66 kg (1.45 lb)
201075	SL FastLink Anchor Strap	X-Large	305 cm (10 ft)	0.76 kg (1.68 lb)
201052	SL Anchor Strap	Small	91 cm (3 ft)	0.36 kg (0.8 lb)
201053	SL Anchor Strap	Medium	152 cm (5 ft)	0.44 kg (0.96 lb)
201054	SL Anchor Strap	Large	213 cm (7 ft)	0.5 kg (1.11 lb)
201055	SL Anchor Strap	X-Large	305 cm (10 ft)	0.61 kg (1.34 lb)
201056	SL Anchor Strap	XX-Large	457 CM (15 ft)	0.78 kg (1.73 lb)
201042	SL Variable Anchor Strap	n/a	91-213 cm (3-7 ft)	0.86 kg (1.89 lb)